

COLTECH TRANSELAST SOLVENT

TECHNICAL DATA SHEET

Date: 15.03.2015 - Version 3

Solvent - Polyurethane Cleaner

Product description	Advantages
COLTECH TRANSELAST SOLVENT, is a special solvent for use with the COLTECH TRANSELAST	 □ Excellent solubility □ Suitable for use by hand application □ Over 10 years of positive feedback worldwide.
Jses	Consumption
COLTECH TRANSELAST SOLVENT is a special solvent for:	4-8% by weight
 use in combination with the COLTECH TRANSELAST cleaning solvent used to dissolve uncured polyurethane adhesives 	

Packaging

COLTECH TRANSELAST SOLVENT is supplied in 16 kg, 4 kg and 1kg pails. Pails should be stored in dry and cool rooms for up to 18 months. Protect the material against moisture and direct sunlight. Storage temperature: 50-300C. Products should remain in their original, unopened containers, bearing the manufacturer's name, product designation, batch number and application precaution labels.

Safety measures

Flammable. Please study the Material Safety Data Sheet. PROFESSIONAL USE ONLY

Our technical advice for use, whether verbal, written or in tests, is given in good faith and reflect the current level of knowledge and experience with our products. When using our products, a detailed object-related and qualified inspection is required in each individual case in order to determine whether the product and for application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults; correct application of our products therefore falls entirely within your scope of liability and responsibility. We will, of course, provide products of consistent quality within the scope of our General Conditions of Sale and Delivery. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. Values in this technical data sheet are given as examples and may not be regarded as specifications contact our R+D department. The new edition of the technical data sheet supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practice.



