

MODELO	MATERIAL	MASA (Kg)	SUPERFICIE (MM)	DINGHY KAYAK	5M 16'	6M 20'	7M 23'	8M 26'	9M 30'	10M 33'	11M 36'	12M 39'	13M 42'	14M 46'	15M 50'
AKP1ST	ACERO INOXIDABLE	1,3	16600	●●●	●										
AKP4ST	ACERO INOXIDABLE	4,4	35000		●●●	●●									
AKP4AL	ALUMINIO	1,5	35000		●●●	●●									
AKP6ST	ACERO INOXIDABLE	6,9	43200			●●●	●●●	●●							
AKP6AL	ALUMINIO	2,3	43200		XXX	●●●	●●●	●●							
AKP9ST	ACERO INOXIDABLE	9,9	62300					●●●	●●●	●●					
AKP9AL	ALUMINIO	4,0	62300			XXX	XXX	●●●	●●●	●●					
AKP14ST	ACERO INOXIDABLE	14,4	75300							●●●	●●●	●●			
AKP14AL	ALUMINIO	6,1	75300					XXX	XXX	●●●	●●●	●●			
AKP17ST	ACERO INOXIDABLE	17,2	89700									●●●	●●●	●●	
AKP17AL	ALUMINIO	7,2	89700							XXX	XXX	●●●	●●●	●●	
AKP23ST	ACERO INOXIDABLE	23,8	98500											●●●	●●
AKP23AL	ALUMINIO	10,6	98500									XXX	XXX	●●●	●●

●
●●
●●●
XXX

TAMAÑO SUFICIENTE EN CONDICIONES DE BUEN TIEMPO (DE DÍA)

TAMAÑO ADECUADO PARA CONDICIONES NORMALES

TAMAÑO ACONSEJADO - USO GENERAL EN TODO TIPO DE CONDICIONES

TAMAÑO ACONSEJADO COMO ANCLA LIGERA DE RESERVA

COMO ANCLA DE TORMENTA SE RECOMIENDA EL TAMAÑO SUPERIOR AL ACONSEJADO

