



## MATERIAL SAFETY DATA SHEET

### COMPANY INFORMATION

Trac Ecological Marine Products & Services  
1103 Old Griffin Road  
Dania, FL 33004  
Phone: (954) 987-2722 Fax: (954) 583-4933

### MSDS INFORMATION

Preparation Date: 05/08/2014  
Supersedes: 09/29/2004  
Prepared By: Security Committee  
Phone: (954) 987-2722

### PRODUCT INFORMATION

Product name/Number: **Trac Sew-Clean 1218-M**  
Trade Name – **Sew-Clean**  
Product Description: (product use): Uric Scale remover

## SECTION I – COMPOSITION / INFORMATION ON INGREDIENTS

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS). Unlisted ingredients are not "hazardous" per the OSHA standard and /or are not found on the WHMIS ingredient disclosure list.

Hazardous ingredients	: Phosphoric Acid 85%	<b>FLAMMABILITY</b>	: <0 >
Approx. concentration. (%)	: 5% -20%	<b>REACTIVITY</b>	: <0 >
#CAS – NA or UN	: 7664 – 38-2	<b>HEALTH</b>	: <1 >
DL 50 (specific type and way)	: 3,500 mg/kg		
Limit of exposition	: none		

## SECTION II – FIRE AND EXPLOSION HAZARD DATES

Inflammability	: ( ) yes	( x ) no
If yes, in which conditions?		
Extinguishing media	: water - foam - powder, dry chemical.	
Special method	: none	
Flash point / method	: none close cup	
Flammability limits in air (% per volume)	: inferior: N/A	superior: N/A
Temperature auto ignition(°F)	: N/A	
Class of flammability THD	: N/A	
Unusual fire and explosion hazard	: none	
Explosion data	: none	
Sensibility of chemical impact	: none	
Combustion rate	: N/A	
Sensibility of electrostatic discharge	: N/A	

## SECTION III - PHYSICAL CHARACTERISTICS

Physical state	: ( ) GAS	( x ) LIQUID	( ) SOLID
Odor and appearance	: Clear / light amine odor		
Threshold odor	: N/A		
Density	: 1.14		
Vapor pressure (mm Hg)	: 14mm hg/70°F		
Vapor density (air = 1)	: N/A		
Evaporation rate	: Same as water		
Boiling point	: 300°F		
Freezing point (°F)	: 30°F		
Solubility in water (70°F)	: Complete		
pH	: 1		

Volatile organic compounds (VOC) contents: no VOC contents

## SECTION IV - TRANSPORTATION INFORMATION

Transportation: Class 55  
Not regulated



## SECTION V – REACTIVITY DATA

Chemical stability : ( x ) yes ( ) no  
If yes, in which conditions? : if store at the recommended temperature

Incompatibility ( Materials to avoid): Avoid contact with strong Alkaline bases because high heat of reaction can generate steam.  
Hazardous Decomposition Materials: None  
Hazardous Polymerization: None  
Conditions to Avoid for Polymerization: None described  
Stability Considerations: Stable  
Conditions to Avoid for Stability: None

## SECTION VI – POTENTIAL HEALTH EFFECTS

Eyes: Eye contact with liquid product may cause irritation.  
Skin: Prolonged or repeated contact with liquid product may cause light irritation.  
Inhalation: Exposure to vapors in poorly ventilated areas may cause light irritation of the nose.  
Ingestion: Not an anticipated route of exposure. Small amounts are not anticipated to be harmful.

## SECTION VII – TOXICITY DATA

Chronic effects of exposure to the product : none  
Irritations : none  
Exposition limit : see section II  
CL50 of product : N/A  
Sensibility : N/A  
Synergic Material  
- Carcinogenicity effects : none  
- Harmful effects of reproduction : none  
- Teratogenes effects : none  
- Mutageny effects : none

## SECTION VIII - FIRST AID MEASURES

Skin: wash with water for a few minutes  
Eyes: rinse with water for a few minutes, if irritation persist consult a physician  
Ingestion: drink one or two glasses of water or milk. Do not induce vomiting consult a physician if stomach ache persist.  
General recommendation: none

## SECTION IX – SPILL OR LEAK PROCEDURES

Small Spills: Spill and lead disposal procedure. Rinse with water  
Large Spills: Should be absorbed by dirt or other absorbents for disposal. Must conform to Federal, State and Municipal regulations.

## SECTION X - PERSONAL PROTECTION

Protection equipment:  
- gloves : rubber gloves  
- respiration protection : none  
- eyes protection : goggle  
- shoes : normal  
- clothing : normal  
- control mechanic device : none

## SECTION XI – SPECIAL PRECAUTIONS

**Precautions to be taken in handling and storing:** Store drums away from excessive heat.